

PRODUCT SPECIFICATIONS AND GUIDELINES

Roofing Nail – HDG & EG



TECHNICAL	Length x Thick (inch)	Penny Length	Gauge (W&M)	Head Diameter	Ring Shank Length, MIN	ASTM F1667 Bend Yield*
Smooth Shank	1/2 x .120	-	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	3/4 x .120	-	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	7/8 x .120	-	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	1 x .120	2d	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	1-1/4 x .120	3d	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	1-1/2 x .120	4d	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	1-3/4 x .120	5d	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	2 x .120	6d	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	2-1/2 x .120	8d	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	3 x .120	10d	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	3-1/2 x .120	-	11	Ø 0.375 in	-	100,000 psi
Smooth Shank	* ASTM F1667 Bend Yield is a minimum average value appropriate for non-hardened products only					

PRODUCT	Length x Thick (inch)	Approximate QTY	Pack Size	Master Pack	EG – SKU	HDG – SKU
Smooth Shank	1/2 x .120	21,200	50# Bulk	1 pail	TOP0132012TS	—
Smooth Shank	3/4 x .120	16,150	50# Bulk	1 pail	TOP0132032TS	—
Smooth Shank	7/8 x .120	14,400	50# Bulk	1 pail	TOP0132042TS	—
Smooth Shank	1 x .120	13,050	50# Bulk	1 pail	TOP0132052TS	—
Smooth Shank	1-1/4 x .120	10,450	50# Bulk	1 pail	TOP0132072TS	—
Smooth Shank	1-1/2 x .120	9700	50# Bulk	1 pail	TOP0132092TS	—
Smooth Shank	1-3/4 x .120	7750	50# Bulk	1 pail	TOP0132112TS	—
Smooth Shank	2 x .120	6800	50# Bulk	1 pail	TOP0132132TS	—
Smooth Shank	2-1/2 x .120	5450	50# Bulk	1 pail	TOP0132152TS	—
Smooth Shank	3 x .120	4650	50# Bulk	1 pail	TOP0132172TS	—
Ring Shank	2 x .120	6800	50# Bulk	1 pail	—	TOP0172132TS
Ring Shank	2-1/2 x .120	5450	50# Bulk	1 pail	—	TOP0172152TS
Ring Shank	3 x .120	—	50# Bulk	1 pail	—	TOP0172192TS
Ring Shank	3-1/2 x .120	—	50# Bulk	1 pail	—	TOP0172192TS
Smooth Shank	3/4 x .120	—	5# box	—	TOP132035TS	—
Smooth Shank	7/8 x .120	—	5# box	—	TOP132045TS	—
Smooth Shank	1 x .120	—	5# box	—	TOP132055TS	—
Smooth Shank	1-1/4 x .120	—	5# box	—	TOP132075TS	—
Smooth Shank	1-1/2 x .120	—	5# box	—	TOP132095TS	—
Smooth Shank	1-3/4 x .120	—	5# box	—	TOP132115TS	—
Smooth Shank	2-1/2 x .120	—	5# box	—	TOP132155TS	—
Smooth Shank	3 x .120	—	5# box	—	TOP132175TS	—

FUNCTION: To Be Used For:

- Asphalt shingles
- Insulation boards
- Felt to wood substrate

FEATURES:


- Hand Driven Fasteners meet or exceed the ASTM F1667 Standard (if applicable)

CORROSION:

- Hot Dip Galvanized (HDG) in accordance with ASTM A153 Class D standards for high level corrosion resistance
- Electro Galvanized (EG) in accordance with ASTM A641 standards for low level corrosion resistance

CAUTION:

- Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener
- All materials and finish options shall be used in accordance with the recommendation of the treated lumber manufacturer



Scan QR Code
for additional
information.